



| Model                                 | EY363-240W-20° | EY363-240W-30° | EY363-240W-60° |
|---------------------------------------|----------------|----------------|----------------|
| Power Consumption (W)                 | 240            |                |                |
| Luminaire Flux ± 5%(lm)               | 31748          | 38400          | 38462          |
| System Efficiency ± 5% (lm/W)         | 133            | 159            | 160            |
| CCT(K)                                | 5000           |                |                |
| Power Factor (PF)                     | ≥ 0.98         |                |                |
| Net Weight /pc (kg)                   | 7.7            |                |                |
| Gross Weight (kg)                     | 8.40           |                |                |
| Product Dimension LxWxH(mm)           | 442x 371x 193  |                |                |
| Individual Carton Dimension LxWxH(mm) | 458x 338x 225  |                |                |

| Model                                 | EY363-320W-20° | EY363-320W-30° | EY363-320W-60° |
|---------------------------------------|----------------|----------------|----------------|
| Power Consumption (W)                 | 320            |                |                |
| Luminaire Flux ± 5%(lm)               | 41843          | 48500          | 49478          |
| System Efficiency ± 5% (lm/W)         | 131            | 153            | 155            |
| CCT(K)                                | 5000           |                |                |
| Power Factor (PF)                     | ≥ 0.98         |                |                |
| Net Weight /pc (kg)                   | 8.10           |                |                |
| Gross Weight (kg)                     | 9.10           |                |                |
| Product Dimension LxWxH(mm)           | 442x 371x 193  |                |                |
| Individual Carton Dimension LxWxH(mm) | 458x 338x 225  |                |                |

| Model                                 | EY363-400W-20° | EY363-400W-30° | EY363-400W-60° |
|---------------------------------------|----------------|----------------|----------------|
| Power Consumption (W)                 | 400            |                |                |
| Luminaire Flux ± 5%(lm)               | 54000          | 58400          | 59200          |
| System Efficiency ± 5% (lm/W)         | 135            | 146            | 148            |
| CCT(K)                                | 5000           |                |                |
| Power Factor (PF)                     | ≥ 0.97         |                |                |
| Net Weight /pc (kg)                   | 18.40          |                |                |
| Gross Weight (kg)                     | 19.90          |                |                |
| Product Dimension LxWxH(mm)           | 746x406x240    |                |                |
| Individual Carton Dimension LxWxH(mm) | 805x 370x260   |                |                |

| Model                                 | EY363-500W-20° | EY363-500W-30° | EY363-500W-60° |
|---------------------------------------|----------------|----------------|----------------|
| Power Consumption (W)                 | 500            |                |                |
| Luminaire Flux ± 5%(lm)               | 67713          | 73500          | 73978          |
| System Efficiency ± 5% (lm/W)         | 135            | 146            | 148            |
| CCT(K)                                | 5000           |                |                |
| Power Factor (PF)                     | ≥ 0.97         |                |                |
| Net Weight /pc (kg)                   | 18.40          |                |                |
| Gross Weight (kg)                     | 19.90          |                |                |
| Product Dimension LxWxH(mm)           | 746x406x240    |                |                |
| Individual Carton Dimension LxWxH(mm) | 805x 370x260   |                |                |